REPORT DOCUMENTATION PAGE					Form Approved
Public reporting burden for	r this collection of information is	estimated to average 1 hour per	response, including the time for re	eviewing instructions, s	OMB No. 0704-0188
I Including cugagetions for a	rodunina thia bullet a Decel		garang tina bu	den esumate or any o	IDEL ASDECT Of this collection of information
collection of information if	it does not display a currently v	alid OMB control number. PLEAS	thstanding any other provision of	law, no person shall be	ns and Reports (0704-0188), 1215 Jefferson Davis e subject to any penalty for failing to comply with a
1. REPORT DATE	(DD-MM-YYYY)	2. REPURITYPE		III TO THE ABOVE A	B. DATES COVERED (From - To)
4. TITLE AND SUB	TITI E	Technical Paper			
" ITTLE AND GOD	III CE				a. CONTRACT NUMBER
				<u> </u>	FO-16(1-01-C-001)  bb. GRANT NUMBER
				1,	D. GRANT NOWBER
				}-	c. PROGRAM ELEMENT NUMBER
0.445					
6. AUTHOR(S)		•		5	d. PROJECT NUMBER
					BMDO
				5	e. TASK NUMBER
					<u>sb</u> ru
				5	f. WORK UNIT NUMBER
7. PERFORMING O	RGANIZATION NAME	S) AND ADDRESS(ES)			
		(O) AND ADDRESS(ES)		8	. PERFORMING ORGANIZATION
			•	"	icroni
					•
					:
0.0000000000000					
9. SPONSORING / N	MONITORING AGENC	/ NAME(S) AND ADDRE	SS(ES)	1	0. SPONSOR/MONITOR'S
				A	CRONYM(S)
Air Force Research	h Laboratory (AFMO	C)			
AFRL/PRS				-	1. SPONSOR/MONITOR'S
5 Pollux Drive				j'	NUMBER(S)
Edwards AFB CA 93524-7048					NOMBER(S)
12. DISTRIBUTION /	AVAILABILITY STAT	MENT			
A 16 11					
Approved for publi	ic release; distributio	n unlimited.			
40 01150	**				·
13. SUPPLEMENTAI	RY NOTES			<del></del>	
14. ABSTRACT					
			•		
			•		
5. SUBJECT TERMS	3	***************************************			
6. SECURITY CLASS	SIFICATION OF		T 42 1 100 - 1		
Jaconin CLAS	on Ioanon of:		17. LIMITATION OF ABSTRACT	18. NUMBER	19a. NAME OF RESPONSIBLE
			OI VIDGILWO!	OF PAGES	PERSON Leilani Piahardaan
. REPORT	b. ABSTRACT	c. THIS PAGE			Leilani Richardson  19b. TELEPHONE NUMBER
T1000			$\left  \begin{array}{c} A \end{array} \right $		(include area code)
nclassified	Unclassified	Unclassified			(661) 275-5015

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. 239.18

Suparate tens ac endered

## MEMORANDUM FOR PRS (Contractor Publication)

FROM: PROI (STINFO)

10 January 2002

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-TP-2002-007
Gary Cheng (UAB); Curtis Johnson & Jeff Muss (Sierra), "Swirl Coaxial Injector Development, Part II:
CFD Modeling"

(Deadline: 15 Feb 2002)

JANNAF JPC (Destin, FL, 8-12 April 2002)

(Statement A)

b.) military/national critical technology, c.) export c d.) appropriateness for release to a foreign nation, a Comments:	and e.) technical sensitivity and/or economic sensitivity.
Signature	Date
and/or b) possible higher headquarters review.  Comments:	fairs Office for: a.) appropriateness for public release
Signature	
Comments:	c.) format and completion of meeting clearance form if required
Signature	Date
4. This request has been reviewed by PR for: a.) tecappropriateness of distribution statement, d.) techninational critical technology, and f.) data rights and Comments:	

APPROVED/APPROVED AS AMENDED/DISAPPROVED

PHILIP A. KESSEL Date
Technical Advisor
Space and Missile Propulsion Division

20021119 102

## Swirl Coaxial Injector Development Part II CFD Modeling

Gary Cheng, ME Dept., UAB Curtis Johnson and Jeff Muss, Sierra Engineering, Inc.

## Abstract

Injector design is crucial to obtain long life and provide high energy release efficiency in the main combustion chamber. Introducing a swirl component in the injector flow can enhance the propellant mixing and thus improve engine performance. Therefore, swirl coaxial injectors show promise for the next generation of high performance staged combustion rocket engines utilizing hydrocarbon fuels. These injectors swirl liquid fuel around a gaseous oxygen core. This work develops a design methodology, utilizing both high-pressure cold-flow testing and uni-element hot-fire testing to create a high performing, long life swirl coaxial injector for multi-element combustor use. Several swirl coax injector configurations were designed and fabricated by Sierra Engineering, and tested at the Propulsion Directorate of the Air Force Research Lab. Both cold-flow and hot-fire tests were conducted. CFD analyses have been performed to assess the ability of CFD to provide detailed insight into the flowfield and improve our understanding of the underlying flow characteristics of an optimized injector design. Both cold-flow and hot-fire analyses were completed. The CFD code utilized was the FDNS-RFV code with the homogeneous real-fluid model employed to simulate the spray combustion phenomena for both the cold flow and hot fire conditions. Initial results show that large scale phenomenology was predicted well by the cold-flow CFD analysis (see Figure 1). Detail flow-field characteristics will be compared when the CFD analyses are completed that match actual test operating conditions. The FDNS-RFV code has been widely employed by NASA MSFC to analyze various flow problems of rocket engines. Analysis and test comparisons will be presented and an assessment of the utility of the analyses will be discussed.

Mass Flux Distributions of Fuel at Various Axial Locations (Swirl Injector #1)

(a)  $\times = 0^1$ (b)  $\times = 2^n$ (c)  $\times = 3^1$ (c)  $\times = 3^1$ (c)  $\times = 3^1$ (d)  $\times = 0^1$ (e)  $\times = 3^1$ (f)  $\times = 0^1$ (g)  $\times = 0^1$ (h)  $\times = 0^1$ (c)  $\times = 0^1$ (d)  $\times = 0^1$ (e)  $\times = 0^1$ (f)  $\times = 0^1$ (g)  $\times = 0^1$ (h)  $\times = 0^1$ (g)  $\times = 0^1$ (h)  $\times = 0^1$ (g)  $\times = 0^1$ 

Figure 1. FDNS analysis of the Mass Flux Distribution for a Cold-Flow Injector Test.

0.2

0.3